

# GOULD <-----> ASCO

CROSS REFERENCE FOR 2 - WAY SOLENOID VALVES

**NORMALLY CLOSED**

*GOULD VALVES: Piston-Pilot Operated <-> ASCO VALVES: Both Piston-Pilot & Diaphragm.*

AIR - WATER - GENERAL SERVICE					
GOULD VALVE TYPE	BRONZE			STAINLESS STEEL	
	M-3V	Q-3V <small>(to 250psi)</small>	Q-3T <small>(to 400psi)</small>	K (303)	KX (316)
1/8"	N/A	N/A	N/A	N/A	N/A
1/4"	N/A	N/A	N/A	N/A	N/A
3/8"	8210G1	8210G6	8210G6	*8210G36	N/A
1/2"	8210G2	8210G7	8210G7	*8210G37	N/A
3/4"	8210G9	8210G3	8210G3	*8210G88	N/A
1"	8210G4	*8210B27	*8210B27	*8210D89	N/A
1 1/4"	8210G8	8210G8	8210G8	N/A	N/A
1 1/2"	8210G22	8210G22	8210G22	N/A	N/A
2"	8210G100	8210G100	8210G100	N/A	N/A
2 1/2"	-- --	8210G101	8210G101	-- --	-- --
3"	-- --	8210B51	8210B51	-- --	-- --

STEAM SERVICE			
BRONZE			STAINLESS <small>(303)</small>
M-1-3EP <small>(to 50psi)</small>	M-1-3T <small>(to 125psi)</small>	Q-1-3T <small>(to 200psi)</small>	K-1 <small>(to 200psi)</small>
N/A	N/A	N/A	N/A
8220G1	8220G19	N/A	N/A
8220G3	8220G21	N/A	*8222C87
8220G5	8220G23	8222G5	*8222C88
8220G7	8220G25	822299	8222B89
8220G9	8220G27	N/A	N/A
8220G11	8220G29	N/A	N/A
8220G13	8220G31	N/A	N/A
-- --	8220G33	8220G33	-- --
-- --	N/A	N/A	-- --

\*Denotes ASCO Diaphragm Valve [GOULD Valve requires 5 psi Minimum Pressure Differential]

**NORMALLY CLOSED -- DIRECT ACTING**

AIR - WATER - GENERAL SERVICE						
GOULD VALVE TYPE	BRONZE			STAINLESS STEEL		
	B3-21	QD	F & FST	K D	<small>(303)</small> G & GST	<small>(316)</small> G X
1/8"	-- --	-- --	8262G1	-- --	8262G12	N/A
1/4"	8262G202	-- --	8262G19	-- --	8262G80	N/A
3/8"	8263G2	8030G10	8263G2	8030G64	8263G330	N/A
1/2"	-- --	8030G16	-- --	8030G66	-- --	N/A
3/4"	-- --	8030G3	-- --	8030G63	-- --	N/A
1"	-- --	N/A	-- --	-- --	-- --	N/A

STEAM SERVICE			
BRONZE		STAINLESS STEEL	
BH-19	F-1	<small>(303)</small> G-1	<small>(316)</small> GX-1
8263G58	N/A	N/A	N/A
8263G300	N/A	N/A	N/A
8263G305	N/A	8263G318	N/A

--- -- This pipe size is not available  
N/A ASCO does not offer direct comparison

**NOTES:**

These comparisons are for Reference ONLY. Consult J.D. Gould Company for specific Solenoid Valve applications.  
GOULD valve designations followed by "-2" and ASCO valve designations preceded by "EF" are NEMA 7

# GOULD <-----> ASCO

## CROSS REFERENCE FOR 2 - WAY SOLENOID VALVES

### NORMALLY OPEN

**GOULD VALVES: Piston-Pilot Operated & Direct Acting <-> ASCO VALVES: Piston-Pilot & Diaphragm**

AIR - WATER - GENERAL SERVICE							STEAM SERVICE				
GOULD VALVE TYPE	Bronze		304 Stainless Steel		316 Stainless Steel		Bronze		Stainless Steel		
	QR-3B <small>(piston-pilot)</small>	FR <small>(direct acting)</small>	GR <small>(direct acting)</small>	KR <small>(piston-pilot)</small>	GRX <small>(direct acting)</small>	KRX <small>(piston-pilot)</small>	QR-1-3T <small>(piston-pilot)</small>	FR-1 <small>(direct acting)</small>	GR-1 <small>(direct acting)</small>	KR-1 <small>(piston-pilot)</small>	
P I P E S I Z E	1/8"	N/A	8262G31 8262G91	8262G94 8262G35	N/A	N/A	N/A	N/A	N/A	N/A	
	1/4"	N/A	8262G260 to G265	8262G130 to G152	N/A	N/A	N/A	N/A	N/A	N/A	
	3/8"	*8210G33	N/A	N/A	N/A	N/A	N/A	822091	N/A	N/A	
	1/2"	*8210G34 8210G12	-- --	-- --	*8210G30	N/A	N/A	822093	-- --	-- --	N/A
	3/4"	*8210G35 8210C13	-- --	-- --	*8210G38	N/A	N/A	822095	-- --	-- --	N/A
	1"	*8210B57 8210D14	-- --	-- --	N/A	N/A	N/A	822097	-- --	-- --	N/A
	1 1/4"	*8210B58 8210D18	-- --	-- --	N/A	N/A	N/A	822099			
	1 1/2"	*8210B59 8210D32	-- --	-- --	N/A	N/A	N/A	8220101			
	2"	8210103	-- --	-- --	N/A	N/A	N/A	8220103			
	2 1/2"	8210104	-- --	-- --	-- --	-- --	-- --	8220105			
3"	N/A	-- --	-- --	-- --	-- --	-- --	N/A				

\*Denotes ASCO Diaphragm Valve [GOULD Valve requires 5 psi Minimum Pressure Differential]

**LEGEND:**

-- -- Pipe Size not offered for particular GOULD VALVE type or ASCO cross-reference  
 N/A ASCO does not offer a direct comparison to this GOULD VALVE

**NOTES:**

These comparisons are for Reference use ONLY. Consult J.D. Gould Company for specific Solenoid Valve Applications.

GOULD valve designations followed by "-2" and ASCO valve designations preceded by "EF" are NEMA 7