

CROSS REFERENCE OF ATKOMATIC TO J D GOULD

CROSS REFERENCE FOR 2 - WAY SOLENOID VALVES

BRONZE NORMALLY CLOSED

GOULD VALVES: Piston-Pilot Operated <-> ATKOMATIC VALVES: Piston-Pilot Operated

AIR - WATER - LT. OIL - GENERAL SERVICE

PIPE SIZE	SHORTY SERIES		M-3V SERIES	
	ATKOMATIC	CV	GOULD	CV
1/8"	N/A	N/A	M-3V	1.3
1/4"	JJ-200-Q	1.4	M-3V	2.1
3/8"	JJ-300-Q	2.7	M-3V	2.3
1/2"	JJ-400-Q	3.5	M-3V	3.9
3/4"	JJ-500-Q	7.5	M-3V	5.1
1"	JJ-600-Q	9.1	M-3V	11.6
1-1/4"	JJ-700-Q	19.5	M-3V	12.1
1-1/2"	JJ-800-Q	21	M-3V	26
2"	JJ-900-Q	46	M-3V	48

NOTE Use Type M4-3V for DC voltages & 12 or 24V 60 Hz.
Refer to Bulletin 120-M Series.

*** Required ordering information for J D Gould M-3V
*Pipe Size
*Pressure - Must specify (5-125 psi or 10-250 psi)
*Voltage

*** **NOTES:**
1 Contact Factory for optional features available for J D Gould valves.
2 J D Gould coils for above valves are rated NEMA 4X (Standard)
3 J D Gould above valves are UL & CSA listed for the following voltages,120,240,480,120/240(dual voltage) VAC,50/60hz. 26 Watts max.
4 Dual voltage coil (120/240,50/60) for ease of stock

STEAM SERVICE

PIPE SIZE	HOTSHOT SERIES		M-1-3T SERIES	
	ATKOMATIC	CV	GOULD	CV
1/8"	N/A	N/A	M-1-3T	1.3
1/4"	HS-200-Q	1.4	M-1-3T	2.1
3/8"	HS-300-Q	2.7	M-1-3T	2.3
1/2"	HS-400-Q	3.5	M-1-3T	3.9
3/4"	HS-500-Q	7.5	M-1-3T	5.1
1"	HS-600-Q	9.1	M-1-3T	11.6
1-1/4"	HS-700-Q	19.5	M-1-3T	12.1
1-1/2"	HS-800-Q	21	M-1-3T	26
2"	N/A	N/A	M-1-3T	48

NOTE Use Type M4-1-3T for DC voltages & 12 or 24V 60 Hz.
Refer to Bulletin 120-M Series.

*** Required ordering information for J D Gould M-1-3T
*Pipe Size
*Voltage
For 50 psi maximum, we recommend Type M-1-3EP.

CROSS REFERENCE OF ATKOMATIC TO J D GOULD

CROSS REFERENCE FOR 2 - WAY SOLENOID VALVES

BRONZE NORMALLY CLOSED

GOULD VALVES: Piston-Pilot Operated <-> ATKOMATIC VALVES: Piston-Pilot Operated

AIR - WATER - LT. OIL - GENERAL SERVICE

PIPE SIZE	SHORTY SERIES		M-3V SERIES	
	ATKOMATIC	CV	GOULD	CV
1/8"	N/A	N/A	M-3V	1.2
1/4"	JJ-200-Q	1.4	M-3V	2.2
3/8"	JJ-300-Q	2.7	M-3V	2.5
1/2"	JJ-400-Q	3.5	M-3V	2.8
3/4"	JJ-500-Q	7.5	M-3V	6.8
1"	JJ-600-Q	9.1	M-3V	11.5
1-1/4"	JJ-700-Q	19.5	M-3V	18
1-1/2"	JJ-800-Q	21	M-3V	26
2"	JJ-900-Q	46	M-3V	48

NOTE Use Type M4-3V for DC voltages & 12 or 24V 60 Hz.
Refer to Bulletin 120-M Series.

*** Required ordering information for J D Gould M-3V
*Pipe Size
*Pressure - Must specify (5-125 psi or 10-250 psi)
*Voltage

*** **NOTES:**
1 Contact Factory for optional features available for J D Gould valves.
2 J D Gould coils for above valves are rated NEMA 4X (Standard)
3 J D Gould above valves are UL & CSA listed for the following voltages,120,240,480,120/240(dual voltage) VAC,50/60hz. 26 Watts max.
4 Dual voltage coil (120/240,50/60) for ease of stock

STEAM SERVICE

PIPE SIZE	HOTSHOT SERIES		M-1-3T SERIES	
	ATKOMATIC	CV	GOULD	CV
1/8"	N/A	N/A	M-1-3T	1.2
1/4"	HS-200-Q	1.4	M-1-3T	2.2
3/8"	HS-300-Q	2.7	M-1-3T	2.5
1/2"	HS-400-Q	3.5	M-1-3T	2.8
3/4"	HS-500-Q	7.5	M-1-3T	6.8
1"	HS-600-Q	9.1	M-1-3T	11.5
1-1/4"	HS-700-Q	19.5	M-1-3T	18
1-1/2"	HS-800-Q	21	M-1-3T	26
2"	N/A	N/A	M-1-3T	48

NOTE Use Type M4-1-3T for DC voltages & 12 or 24V 60 Hz.
Refer to Bulletin 120-M Series.

*** Required ordering information for J D Gould M-1-3T
*Pipe Size
*Voltage
For 50 psi maximum, we recommend Type M-1-3EP.